

ULPN-355-50-1-30-R

Ultraviolet Nanosecond Fiber Laser

NEW PRODUCT





Applications

- ▶ Materials Processing
- ▶ Micromachining
- ▶ Solar/ Photovoltaic
- ▶ Plastics Marking
- ▶ Texturing
- ▶ Si Ablation
- ▶ Scribing



Features

- ▶ Wavelength 355 nm
- ▶ Pulse Energy >50 µJ
- ▶ Pulse Duration 1.5 ns
- ▶ Peak Power >40 kW
- ▶ Beam Quality M²<1.8
- ▶ Repetition Rate up to 600 kHz
- ▶ Record Wall-plug Efficiency
- ▶ Air-cooled
- ▶ Rugged Design

IPG Photonics' NEW ULPN-R Series ultraviolet nanosecond fiber lasers provide high peak power with scalable average output power up to 30 W, 1.5 ns pulse duration at full operational repetition rate range of 10-600 kHz. The all fiber format allows for the adjustment of pulse energy and/or pulse repetition rate without affecting any of the output beam parameters. IPG's novel fiber laser is much more efficient and compact than conventional lasers now on the market, and is ideal for applications in the solar/photovoltaic arena, resistor trimming and marking of transparent materials. The short wavelength, short pulse duration and high peak power result in very small heat affected zone.



ULPN-355-50-1-30-R

Ultraviolet Nanosecond Fiber Laser


Optical Characteristics	
Wavelength, nm	355±5
Average Power, W	30
Pulse Energy, µJ	>50
Pulse Duration, ns	1-1.8
Peak Power, kW	>40
Repetition Rate, kHz	10-600

<1.8

General Characteristics

Beam Quality, M²

Control Unit Dimensions, mm	518 x 449 x 176
Optical Head Dimensions, mm	165 x 240 x 65
Cooling	Air-cooled
Supply Voltage, VAC	100-240, 50-60 Hz
Power Consumption, W	380



- +1 (508) 373-1100; sales.us@ipgphotonics.com
- +49 2736 44200; sales.europe@ipgphotonics.com (all European Inquiries)

www.ipgphotonics.com

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind IPG only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with use of a product or its application. IPG, IPG Photonics, The Power to Transform and IPG Photonics' logo are trademarks of IPG Photonics Corporation. © 2014-16 IPG Photonics Corporation. All rights reserved.



2

The Power to Transform®